

TYPE PPE 2000V PORTABLE POWER CABLE ASSEMBLIES

Rated up to 2000V
UL and MSHA approved



CONSTRUCTION

- Conductors** – Highly flexible stranded No. 30 bare copper
- Separator** – High strength fiber braid separator between the conductor and insulation
- Insulation** – High grade RoHS compliant Thermoplastic Elastomer (TPE)
- Jacket** – Black heavy-duty RoHS compliant Thermoplastic Elastomer (TPE)

TYPE PPE ASSEMBLIES

Part Number	AWG	Ampacity* 40°C Ambient Temp.	Description
		A	
G02BXXXAMBFB	#2	190	#2 Type PPE with Black Male & Female CAM Connectors
G20BXXXAMBFB	2/0	300	2/0 Type PPE with Black Male & Female CAM Connectors
G40BXXXAMBFB	4/0	405	4/0 Type PPE with Black Male & Female CAM Connectors

* Ampacity – Free air measure; Based on continuous duty at 90°C conductor temperature no.
Note: XXX in part number equals desired length: 025, 050, 075, 100

TYPE PPE PIGTAILS

Part Number	Description
G40B006PMB	4/0 Type PPE 6' Pigtail with Black Male CAM Connector and Bare
G40B006PFB	4/0 Type PPE 6' Pigtail with Black Female CAM Connector and Bare
G40B003PMB	4/0 Type PPE 3' Pigtail with Black Male CAM Connector and Bare
G40B003PFB	4/0 Type PPE 3' Pigtail with Black Female CAM Connector and Bare

Termination Options Available: Lug, Center Pin, Offset Pin, Shoo Pin, Barrel Pin

Type PPE Portable Power Cable Assemblies are designed for heavy-duty industrial power applications that require temporary or permanent power including portable generators, grounding, power extension, and mining and oil drilling

- UL Listed Portable Power Cable made from annealed no. 30 gauge bare copper stranding
- Durable TPE jacket and insulator for maximum flexibility
- UL and MSHA approved
- National Electric Code Article 400
- Can be used in Type W applications
- Incredible resistance to impact and abrasion
- Water, flame, ozone, sunlight, grease, weather, and chemical resistant
- Operating temperatures range from -40°C to 90°C dry

Options

- Custom cable print
- Sequentially marked
- Made-to-order lengths
- Heat shrink logo ID
- Available in black, red, blue, white, green, brown, orange, and yellow jacketed cable



GENERGY HEADQUARTERS
P.O. BOX 10731
LANCASTER, PA 17605

WAREHOUSES
Edmonton, AB
Houston, TX
Jacksonville, FL
Lancaster, PA
Valencia, CA

GENERGYCABLE.COM
Phone 717-584-0375
Fax 717-704-8445
Toll-Free 800-308-1330

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

MADE IN USA