

GENFLEX™ TYPE W 2000V PORTABLE POWER CABLE ASSEMBLIES

Rated up to 2000V
UL, CSA, and MSHA approved



CONSTRUCTION

Conductors – Extra flexible strand copper, ASTM B-172 and ICEA S-75-381

Insulation – Ethylene-propylene rubber (EPR), UL 1072

Jacket – Black heavy-duty CPE thermoset compound, ICEA S-75-381 sec 3.22

Durable Jacket EPR (ethylene-propylene rubber) with black heavy-duty CPE thermoset compound

GenFlex™ Type W Portable Power Cable Assemblies are designed for heavy-duty industrial power applications that require temporary or permanent power including portable generators, grounding, power extension, and mining and oil drilling.

- **UL Listed Portable Power Cable** made from annealed no. 30 gauge bare copper stranding
- **Flexible EPR/CPE single conductor** portable power cable
- **Reinforced strength**
- Incredible **resistance to impact and abrasion**
- **Water, flame, ozone, sunlight, grease, weather, and chemical resistant**
- Operating temperatures range from **-40°C to 90°C dry**

GENFLEX™ TYPE W ASSEMBLIES

| Part Number | AWG | Ampacity* 40°C Ambient Temp. | Description |
|--------------|-----|---------------------------------------|--|
| | | A | |
| W02BXXXAMBFB | #2 | 190 | #2 Type W with Black Male & Female CAM Connectors |
| W20BXXXAMBFB | 2/0 | 300 | 2/0 Type W with Black Male & Female CAM Connectors |
| W40BXXXAMBFB | 4/0 | 405 | 4/0 Type W with Black Male & Female CAM Connectors |

* Ampacity – Free air measure; Based on continuous duty at 90°C conductor temperature no.

Note: XXX in part number equals desired length: 025, 050, 075, 100

GENFLEX™ TYPE W PIGTAILS

| Part Number | Description |
|-------------|---|
| W40B006PMB | 4/0 Type W 6 ft. Pigtail with Black Male CAM Connector and Bare |
| W40B006PFB | 4/0 Type W 6 ft. Pigtail with Black Female CAM Connector and Bare |
| W40B003PMBH | 4/0 Type W 3 ft. Pigtail with Black Male CAM Connector and Bare |
| W40B003PFBH | 4/0 Type W 3 ft. Pigtail with Black Female CAM Connector and Bare |

Termination Options Available: Lug, Center Pin, Offset Pin, Shoo-Pin, Barrel Pin

Options

- Custom cable print
- Sequentially marked
- Made-to-order lengths
- Heat shrink logo ID



GENERGY HEADQUARTERS

P.O. BOX 10731
LANCASTER, PA 17605

WAREHOUSES

Edmonton, AB
Houston, TX
Jacksonville, FL
Lancaster, PA
Valencia, CA

GENERGYCABLE.COM

Phone 717-584-0375
Fax 717-704-8445
Toll-Free 800-308-1330

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

MADE IN USA