



Durable 60A Pin & Sleeve assemblies provide reliable power for live events, motion pictures, and other theatrical applications.

- Constructed with **IEC 60309 listed Hubbell plug and connector and 4/5 SOOW cable**
- **Corrosion and impact resistant**
- Gasketed sealing ring provides **watertight seal to resist harsh weather and rough working conditions**
- **4" clear heat shrink on both ends**
- Solid one-piece pin construction for **reliable electrical contact**
- Heavy-duty **external cord grips**
- IEC 60309 Pin and Sleeve **watertight for outdoor use**

PIN & SLEEVE EXTENSIONS

Cable	Description	Length	Weight (lbs.)	Part Number
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	5'	11.9	P045B005HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	10'	18.5	P045B010HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	15'	25.1	P045B015HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	25'	38.3	P045B025HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	40'	58.1	P045B040HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	50'	71.3	P045B050HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	75'	104.3	P045B075HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	100'	137.3	P045B100HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	125'	170.3	P045B125HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	150'	203.3	P045B150HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	200'	269.3	P045B200HBL560PC

GENERGY HEADQUARTERS
P.O. BOX 10731
LANCASTER, PA 17603

WAREHOUSES
Edmonton, AB
Houston, TX
Jacksonville, FL
Lancaster, PA
Valencia, CA

GENERGYCABLE.COM
Phone 717-584-0375
Fax 717-704-8445
Toll-Free 800-308-1330

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

MADE IN USA