

50A TWIST-LOCK EXTENSIONS AND TIE-INS

Options

- Custom lengths
- Cable identification

genErgy™



Used to provide temporary power for disaster recovery and industrial applications

- Assembled with **6/4 cable** and black and white **50A Non-NEMA** line of **industrial-grade locking blade connectors**
- Great **impact, sunlight, and chemical resistance**
- Withstands **rough use**
- Connectors feature **one-piece construction** for maximum conductivity
- Also known as **California style cords** and **6/4 spider box cables**
- Brass mounting system for a **safer resistance ground path**

EXTENSIONS AND TIE-INS

Part Number	Male Connector	Female Connector	Cable	Lengths
P064BXXXACSMF	Non-NEMA, 125/250V AC, 3P/4W, Black & White Locking Connector, Industrial Grade, Grounding, California-Style (CS)	Non-NEMA, 125/250V AC, 3P/4W, Black & White Locking Connector, Industrial Grade, Grounding, California-Style (CS)	6/4	25', 50', 75', 100'
P064B005PCSMB	Non-NEMA, 125/250V AC, 3P/4W, Black & White Locking Connector, Industrial Grade, Grounding, California-Style (CS)	Bare	6/4	5'
P064B005PCSFB	Bare	Non-NEMA, 125/250V AC, 3P/4W, Black & White Locking Connector, Industrial Grade, Grounding, California-Style (CS)	6/4	5'

Note: XXX in part number equals desired length: 005, 010, 025, 050, 075, 100

SOOW CABLE

Part Number	AWG	No. of Conductors	Stranding/ Diameter	Nominal Insulation Thickness		Nominal Jacket Thickness		Nominal O.D.		Approx. Weight lbs./1000 ft.	Ampacity* 30°C Ambient Temp.
				in.	mm	in.	mm	in.	mm		A
SOOW6-4	6	4	184/0.0117	0.060	1.52	0.140	3.56	1.05	26.7	785	45.0

*Ampacity – Free air measured; based on continuous duty at 90°C conductor temperature

GENERGY POWER
717.584.0375 Phone
717.704.8445 Fax
800.308.1330 Toll-Free
www.GenErgyCable.com

STOCKING WAREHOUSES
Edmonton, AB
Houston, TX
Lancaster, PA
Orlando, FL
Valencia, CA

EAST COAST HEADQUARTERS
1812C OLDE HOMESTEAD LANE
LANCASTER, PA 17601

WEST COAST OPERATIONS
28365 CONSTELLATION ROAD
VALENCIA, CA 91355

MADE IN USA