

NEMA WIRING DEVICE EXTENSIONS

Options

- Custom lengths
- Custom cable identification
- Non-wetguard connectors

genEnergy™



20A extra hard usage cords with plugs and connectors resistant to moisture, chemicals, and environmental concerns so you can use them indoors or outdoors.

- Produced with **SOOW** cord
- **Straight blade, locking, and wetguard** devices available
- **Factory-tested**
- **15A, 20A, and 30A** assemblies
- Heavy-duty **UL** and **CSA** cable
- Excellent **oil, water, abrasion, and UV resistance**
- **Additional gauges** available

WETGUARD LOCKING EXTENSIONS

Rating	Cable	NEMA	Part Number
20A, 125 VAC	12/3 SOOW	L5-20 Locking	P123BXXXL520-WG
20A, 250 VAC	12/3 SOOW	L6-20 Locking	P123BXXXL620-WG
20A, 125/250 VAC	12/4 SOOW	L14-20 Locking	P124BXXXL1420-WG
30A, 125/250 VAC	12/4 SOOW	L14-30 Locking	P124BXXXL1430-WG
30A, 120 VAC	10/3 SOOW	L5-30 Locking	P103BXXXL530-WG
30A, 120 VAC	10/5 SOOW	L21-30 Locking	P105BXXXL2130-WG
20A, 120 VAC	12/5 SOOW	L21-20 Locking	P125BXXXL2120-WG
15A, 120 VAC	12/3 SOOW	L5-15 Locking	P123BXXXL515-WG
30A, 250 VAC	12/3 SOOW	L6-30 Locking	P123BXXXL630-WG
15A, 250 VAC	12/3 SOOW	L6-15 Locking	P123BXXXL615-WG

Note: XXX in part number equals desired length: 005, 010, 0150, 025, 050, 075, 100

GENERGY HEADQUARTERS

P.O. BOX 10731
LANCASTER, PA 17605

WAREHOUSES

Edmonton, AB
Houston, TX
Jacksonville, FL
Lancaster, PA
Valencia, CA

GENERGYCABLE.COM

Phone 717-584-0375
Fax 717-704-8445
Toll-Free 800-308-1330

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

MADE IN USA